CD		CAT	וחו־	$\nabla \mathbf{I} \mathbf{C}$
JI		LAI		L

	Cargo EV Super King EV		
Parameter			
Model Name	Superior EV		
Seating Capacity	Driver only		
Battery	<del>-</del>		
Type &Voltage	Lithium ion & 51.2 V		
Chemistry	LFP		
Battery Capacity	Rated:- 10.24 kWh (200Ah)		
Charger	-		
Capacity	51V/3KW charger Off-board Charger		
Charge Duration (hh:min)	4 hrs		
Motor	<u>-</u>		
Peak Power (kW)	10kW		
Rated Power	4.5 kW		
Peak Torque (Nm)	39 NM		
Vehicle Level Parameter	-		
Weights	-		
GVW	990kg		
Kerb Weight	470kg		
Payload	520		
Suspension & Brakes	-		
Front Suspension	Helical Spring with hydraulic dampener		
Rear Suspension	Rubber spring with hydraulic dampener		
Brake	Drum Brake hydraulically Actuated Internal Expanding Shoe Type Dia-180mm		
Tyre	Front:- 4.0-8" 4PR 70E Rear:- 4.0-8" 4PR 70E		
Transmission	-		
Туре	Synchromesh gearbox with two speed gears & clutch arrangement.		
Performance as per doccuments	-		
Top Speed (km/h)	50		
Typical Driving Range	120 +		
Gradeability	12°		